

NOVUS H.P.LED IN + NOVUS IN BOX

INSTALLATION INSTRUCTIONS FOR LUMINAIRE NOVUS H.P.LED IN + NOVUS IN BOX

1

A. Cut hole on false ceiling

B. Make wiring connection

C. The cable of the driver will be connected to the fixture. Insert driver into the ceiling.

D. Rotate the holding accessories parallel to the box. Insert NOVUS box into the false ceiling.

min 150

38

2

E. The holding system accessories are directed perpendicularly to the box, so as to attach the fixture securely on ceiling.

F. Screw up until the accessories are fixed in false ceiling.

G. Connect the fixture to the cable driver.

3

Push NOVUS fixture into Novus Box, until it clicks into place.

"CLICK"

CAUTION
Wear anti-static gloves before you touch LED systems

* in this instruction, the fitting is with remote driver

USER INSTRUCTIONS

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the main supply is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.
- LED modules are replaced only by the manufacturer.



Last update: OCT 2017