

# FUGA 2 ROUND TRIMLESS

indoor/ profiles

## installation instructions



**1** Cut ceiling

>300

Ø 605/Ø 805/Ø 1005 /Ø 1205

**2** Finish or/and paint the edge of the false ceiling for a better installation result.

! CAUTION  
Make sure you keep the same diameter

**3** Make wiring connections

OFF

OFF

Fit into the false ceiling

**4** Slide the fixture to fit the restraint metal strips

**5** Screw on the fixture all the restraint metal strips

Measure the width of false ceiling and screw the metal strips

hole in case the fixture settle on a plasteboard system


adjust the position of the strip according to this width

**6**

**USER INSTRUCTIONS**

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the mains is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.
- LED modules are replaced only by the manufacturer.

**CAUTION**  
Wear anti-static gloves before you touch LED systems



**CAUTION**  
Replace any cracked shield



**Factory**  
5 Kefalovrisou Str., Monomati, Acharnai, P.O. Box 13677, Athens, Greece | Tel: (+30) 210 6208 230  
E-mail: info@bright.gr | www.bright.gr

IP40

