

# MINI NEXUS GROUND CIRCLE H.P.LED 3 INOX

INSTALLATION INSTRUCTIONS OF LUMINAIRE MINI NEXUS GROUND CIRCLE H.P.LED 3 INOX

**1** Make hole in the ground  
Insert installation box

70 x 70  
Depth: ~73  
Silicone gasket  
Do **not** remove

**2**

Notice ground surface

12/24V

ground installation

**3** Remove the INOX cap

allen wrench No 2.5

**4**

1. Unscrew and remove inner frame part with allen wrench No2.5. (4) screws.
2. Make wiring connections
3. Remove the box screws (2) with allen wrench No 3, and then fit the fixture in the box. Tighten the (2) screws.
4. Fit the fixture frame (inner part). Do not remove silicone gaskets. Tighen (4) screws.
5. Fit the Inox cap and tighten the (4) screws.

allen wrench No 2.5  
Silicone gasket  
Do **not** remove  
allen wrench No 3


## USER INSTRUCTIONS

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the mains is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.
- LED modules are replaced only by the manufacturer.

**CAUTION**  
Replace any cracked shield



**CAUTION**  
Wear anti-static gloves before you touch LED systems



power supply  
**12/24V DC**

**IP67** **CE**

Last updated: August 2016