

SATIS 2

INSTALLATION INSTRUCTIONS FOR LUMINAIRE SATIS 2

1 Installation
In construction phase Build the box in the wall

junction box cap

3 Release the (4) screws with allen wrench. Remove the cap

(4x)

Allen wrench No. 5

5 Release the (2) screws with a screwdriver. Remove the reflector.

7 Screw the luminaire on the box with a screwdriver. Fit the reflector, the glass and the cap cover.

(x4)

2 Cover box with cap to keep it clean.

The hole in the middle enables the removal of the cap.

4 Remove cap and glass cover.

Rubber gasket

Note Do not remove the gasket from glass cover


6 Make wiring connections. Insert luminaire in the junction box. Insert reflector and lamp.

PUSH

USER INSTRUCTIONS

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the mains is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.

CAUTION
Replace any cracked shield



IP65

Date Issued: September 2016